

Flue Cap Extension Kits

826-3179, 3180, 3181, 3182, 3183

In This Kit			
Part #	Kit #	Description	Qty
260-0834	826-3179	Flue cap extension*, 1-vat	1
823-8868	826-3180	Flue cap extension*, 2-vat	1
823-8869	826-3181	Flue cap extension*, 3-vat	1
823-8870	826-3182	Flue cap extension*, 4-vat	1
823-8871	826-3183	Flue cap extension*, 5-vat	1
826-1371	all	Drill-Point Screws, pack	1
819-7075	all	Instructions	1

*Extensions are kit specific; one per kit.

Follow these instructions to install a flue cap extension on a GL30.

1. Remove power from fryer and gain access to the back.
2. Remove screws shown in Figure 1 and retain.
3. Position flue cap extension, ensuring it overlaps the front of the existing flue cap and the flange at the center of the extension grips the edge of the existing flue cap. (See Figures 2 and 4.) The single-vat fryer lacks the brace shown in Figures 3, 4.
4. Fasten the flue cap extension with screws removed in Step 1 and with provided drill-point screws at positions indicated by arrows in Figure 3.
5. Return fryer to hood.



Figure 1: Remove screws at points identified by arrows.



Figure 2: Ensure Flue cap extension overlaps existing flue cap on the front. See arrow



Figures 3,4: Attach flue cap extension with removed screws and provided drill-point screws at positions indicated by arrows. A flange (see photo, right) on the flue cap extension grips the existing flue cap behind the middle brace.

