



FQG80/100/120T COMMISSION FORM GENERAL MARKET

			8700 L	INE AVENUE. Date		'EPOI	RT, LA 711	106	(800) 551-8	3633					
Store Name								– nicia	n							
Store Name Store # (if applicable)							Service Agency									
Address								ess								
AddressCity/State							City/S									
Store Phone ()							Coun		_							
010.0	. 110110					-								1		
FRYER/FIL			FILTER M	TER MODEL NUMBER			SERIAL NUMBE				ER (10	DIGIT)			
_	L.															
	No one is to perform start-up or training unless they are Frymaster trained. Verify Universal hoods have 2" (50mm) of clearance behind fryer □ YES □															
	-		,	•	ince behind	tryer	•					S \square N	1O			
	•	fryer has a 1	•													
<u> </u>	Verify each fryer has a 20-amp 120VAC outlet.															
	Verify gas hose quick disconnect is connected to gas line input on the back of the fryer and verify the other gas input connection is capped.															s input
	Ensure frye	er is level and	properly res	strained in a	ccordance v	vith tl	he operate	or's m	nanua	ıl.						
	Record S	oftware U	B	SI	B1			VIB.					_			
	FIB	Software Ul	IOB_			oqs										
	Ensure Tir	ne and Date	are correct	in setup. R	efer to man	<u>ıual.</u>							-14 -) 	_	C
		te and Perfo sure the filter										L V		30 1		Scan for video
	Demonstra	te Clean and	Filter function	on in the con	troller. Stres	ss th	at it is to b	oe doi	ne da	ily.		į.	e^{it}	灰	ት:	demons
	Demonstra	te the assem	bly of the filt	er pan and f	ilter paper o	r env	elope.					j	, T	10		trations
													•			
		setup as a V	ASTE DISE	POSAL SYS	TFM was it	nowe	er cycled a	after s	setun'	?	□ YES	з п г	NΟ			
	•	clean and dr				p =	,		- СТ	•						
		aurant to ens	-			sitive	or negativ	ve air	· balar	nce						
ā		pan alignme			•		•				ne is fu	llv ena	aged	in the	nan s	suction
	tube. "P" s	hould be disp	layed on the	e controller v	vhen the pai	n is p	ulled out.		F			,	5			
	tube. "P" should be displayed on the controller when the pan is pulled out. Remove old Fryer's Friend from the store if applicable and replace with the new Fryer's Friend.															
	WELBILT KITCHEN CONNECT: For Fryer's equipped with kitchen connectivity capabilities and software, execution of this Commission Form acknowledges the following with regards to Welbilt software and data services: The Fryer is															
					ystem application software (the "KC Solution"). The K0											
as a cloud-based software service. Welbilt uses a third-party cloud-based software hosting from the Fryer. While Welbilt shall use commercially reasonable efforts to require the third-party to require the third-party commercially reasonable efforts to require the third-party commercially reasonable efforts to require the third-party commercially reasonable efforts to require the third-party cloud-based software hosting																
service to implement and utilize appropriate data security safeguards and availability services																
	availability	of the data is	s not warrar	ited or guara	anteed by W	Velbil	t, and We	elbilt s	shall l	have ı	no liabil	lity wit	h resp	ect to	the	acts or
		of the third-pa														
		ility of the da ore, process														
		naintenance,														
		improvemen			, ,	,		,				Ū				
		units are hea ensor rod red						ıs: 6-1	14" W	.C.; LI	P Gas:	11-14"	' W.C.). Ens	sure th	ne pilot
_	•	ual incoming														
	Check burn	ner manifold p	ressure. Re	cord burner	manifold pre	essu	re below.									
	Gas	Vat #1	Vat #2	Vat #3	Vat #4											
Burner	Pressure															
Store Manager / Representative			/e			Prir	nted Name	е								
Signat	ure															
						_ ·										
Technician's Signature						Prir	nted Name	е								



One (1) hour plus travel is allowed for the above, to Commission one system.