## **FRYMASTER**

## **McDonald's Australia**

## **LOV-T Fryer Dispose to Bulk Instructions**

DISPLAY	ACTION
	1. Press the filtration menu button
	2. Select LEFT VAT or RIGHT VAT for split vats.
AUTO FILTRATION  AUTO FILTRATION  MAINTENANCE FILTER  DISPOSE OIL  DRAIN OIL  COMPANN OIL  COMPA	3. Select DISPOSE OIL.
DISPOSE OIL?	4. Press the $\sqrt{(check)}$ button to continue. If the X button is selected, the user returns to the filtration menu.
BULK TANK FULL?	<ol> <li>This message is only displayed if the bull tank is full. Press the √ (check) button to acknowledge and call the bulk oil waste provider. The display returns to OFF.</li> </ol>
DRAINING IN PROGRESS	6. No action required as oil drains into filter pan.
VAT EMPTY?	7. Once the vat is empty, press the $\sqrt{(check)}$ button to continue.
CLEAN VAT COMPLETE?	<ol> <li>Clean the vat with a scrub brush and when complete press the √ (check) button to continue.</li> </ol>
OPEN DISPOSE VALVE	9. Open the left cabinet door and unlock the valve if necessary. Pull the dispose valve completely forward to start disposal.
DISPOSING	10. No action is required while the pump transfers the waste oil from the pan to the bulk oil waste tanks for four (4) minutes.
REMOVE PAN	11. Carefully pull the filter pan from the fryer.
IS PAN EMPTY?	<ul> <li>12. If the filter pan is empty press the √ (check) button. If the pan is not empty, press the X button and return to step 10 after inserting the filter pan.</li> </ul>
INSERT PAN	13. Insert the filter pan.
CLOSE DISPOSE VALVE	<ul> <li>14. Close the dispose valve by pushing the valve handle toward the rear of the fryer until it stops. Relock the valve if required by your manager.</li> </ul>
FILL VAT FROM BULK?	15. The vat is ready to be refilled with oil. Press the √ (check) button to continue otherwise press the X button to exit to step 19.
START FILLING?	16. Press and hold the button to fill the vat. The bulk oil refill pump uses a
PRESS AND HOLD	momentary switch. It only pumps as long as the switch is depressed.
RELEASE BUTTON WHEN FULL	17. Release the button when the vat is filled to the lower fill line.
CONTINUE FILLING?	<ol> <li>Press the √ (check) button to return to step 16 and continue filling. Otherwise press the X button once the vat is full to exit and return to OFF.</li> </ol>
	19. The controller switches off.





09/2019