











# Manual LOV Quick Reference

## Responding to Quick Filter Prompt

Display	Action	
<b>FILTER NOW?</b> alternating with <b>YES NO</b>	After a preset number of cook cycles or time the controller displays <b>FILTER NOW?</b> alternating with <b>YES NO</b> . Press the ✓ ( <b>1 YES</b> ) button.	
<b>SKIM VAT</b> alternating with count-down timer	Skim the vat.	
<b>CONFIRM</b> alternating with <b>YES NO</b>	Press the ✓ ( <b>1 YES</b> ) button to start filtration and ✖ ( <b>2 NO</b> ) to cancel filtration. If <b>NO</b> is selected, the fryer will prompt again after a select number of cooks to filter the oil.	
<b>OPEN DRAIN VALVE</b>	Open the drain valve.	
<b>DRAINING</b> alternating with count-down timer	None required.	
<b>OPEN RETURN VALVE</b> alternating with <b>CONFIRM</b>	Open the return valve and press the ✓ ( <b>1</b> ) button.	
<b>WASHING</b> alternating with count-down timer	None required.	
<b>CLOSE DRAIN VALVE.</b>	Close the drain valve.	
<b>FILLING</b> alternating with count-down timer	None required.	
<b>CLOSE RETURN VALVE WHEN VAT FULL</b> alternating with <b>CONFIRM</b>	Close the return valve when the vat is full and bubbles appear in the oil and press the ✓ ( <b>1</b> ) button.	
<b>OFF</b>		

**Frymaster**

# Daily Filter Pan Cleaning and Preparation

The filter pad in a Manual LOV™ fryer must be replaced at least once daily. In high-volume stores it should be replaced more often.



Replace O-rings every 90 days.

The filter pan must be cleaned daily and the filter pad replaced. Follow these instructions to prepare the filter pan:

Remove and disassemble



- the pan. Discard old filter pad. Clean thoroughly. Leave no water in the pan. Reassemble the pan in this order:
1. Position the inner screen.
  2. Place the filter pad, textured



- side up, in the pan.
3. Position the hold-down ring on the filter pad.
4. Position the crumb tray.
5. Firmly seat the filter pan in the cabinet.